

Door Mounting type



Features


- ♦ IP55 waterproof at external side
- ◆ "One touch" dry run test and dust cleaning
- Optional communication function design
- Easy installation and maintenance from internal side
- ◆ Clear LED status indicator
- ♦ High efficiency and reliable fan modules

Design

- ◆ Air to air heat exchange
- **♦** Door mounted
- ♦ Rated voltage at 48V
- ◆ Complete airtight design for outdoor application
- Drainage hole in the bottom
- Redantant fan quantity design

HEX260PA series

Dimension drawing



Main feature	Unit	Specification
Dimension (H x W x D)	mm	1400 x 650 x 260
Cooling capacity	W/K	260 (MAX.) *Note
Rated voltage	Vdc	48 (TYP.)
Operating voltage range	Vdc	40 ~ 60
Rated current	Α	12.0 (MAX.)
Power consumption	W	576.0 (MAX.)
Operating temperature range	°C	-10 ~ +65
Internal airflow	CFM	940
External airflow	CFM	640
Weight	Kg	37

* Note : The cooling capacity (W/K OR W/°C) is defined as Q/ (T_I-T_A)

Q: Heat dissipation (W) from inside of cabinet

T₁: Return temperature of internal air circuit (K OR °C)

T_A: Ambient temperature of external air circuit (K OR °C)